BookletChart


Intracoastal Waterway Tolomato River to Palm Shores


(NOAA Chart 11485)



A reduced scale NOAA nautical chart for small boaters. When possible, use the full size NOAA chart for navigation.

- ☑ Complete, reduced scale nautical chart
- ✓ Print at home for free
- ☑ Convenient size
- ☑ Up to date with all Notices to Mariners
- ☑ United States Coast Pilot excerpts
- ✓ Compiled by NOAA, the nation's chartmaker.





What are Nautical Charts?

Nautical charts are a fundamental tool of marine navigation. They show water depths, obstructions, buoys, other aids to navigation, and much more. The information is shown in a way that promotes safe and efficient navigation. Chart carriage is mandatory on the commercial ships that carry America's commerce. They are also used on every Navy and Coast Guard ship, fishing and passenger vessels, and are widely carried by recreational boaters.

What is a BookletChart[™]?

This BookletChart is made to help recreational boaters locate themselves on the water. It has been reduced in scale for convenience, but otherwise contains all the information of the full-scale nautical chart. The bar scales have also been reduced, and are accurate when used to measure distances in this BookletChart. See the Note at the bottom of page 5 for the reduction in scale applied to this chart.

Whenever possible, use the official, full scale NOAA nautical chart for navigation. Nautical chart sales agents are listed on the Internet at http://www.NauticalCharts.NOAA.gov.

This BookletChart does NOT fulfill chart carriage requirements for regulated commercial vessels under Titles 33 and 44 of the Code of Federal Regulations.

Notice to Mariners Correction Status

This BookletChart has been updated for chart corrections published in the U.S. Coast Guard Local Notice to Mariners, the National Geospatial Intelligence Agency Weekly Notice to Mariners, and, where applicable, the Canadian Coast Guard Notice to Mariners. Additional chart corrections have been made by NOAA in advance of their publication in a Notice to Mariners. The last Notices to Mariners applied to this chart are listed in the Note at the bottom of page 7. Coast Pilot excerpts are not being corrected.



[Coast Pilot 4, Chapter 12 excerpts]

(254) At **Mile 775.6**, a channel marked by daybeacons and a **250**° lighted range leads west to a protected marina. Berths, electricity, gasoline, diesel fuel, water, ice, pump-out station, marine supplies, and wet storage are available.

(255) Severe shoaling had occurred in the Intracoastal Waterway from **Mile 775** southward to **Mile 780**, including the area crossing St. Augustine Inlet. Mariners are advised to seek local knowledge before

transiting.

(256) The **Vilano Beach** Route A1A bridge: Tidal currents run at angles to the bridge and caution is imperative. A marina on the north side of the bridge has berths, electricity, gasoline, diesel fuel, water, ice and wet storage.

(257) **Matanzas River**. At **Mile 777.9**, Route A1A bridge: Caution is advised because the tidal currents, particularly ebb, run at right angles to the bridge.

(263) At **Mile 788.6, Crescent Beach,** Route 206 bridge: Gasoline may be obtained by shallow-draft boats at a fishing camp south of the bridge. (265) Navigation in the Waterway opposite the breakthrough at Matanzas Inlet at **Mile 794.0** is hazardous during flood and ebb tides. Signs reading "DANGER TURBULENT WATER" have been placed to warn mariners. (266) **Matanzas Inlet.** Route A1A bridge has a clearance of 10 feet. Route A1A bridge crossing **Matanzas River** has a clearance of 12 feet; the one crossing the river 1 mile farther south has a clearance of 12 feet. (267) At **Mile 796.6** is the oceanarium at **Marineland** where marine life are exhibited. On the east side of the waterway a privately marked channel, with a depth of 7 feet leads to the Marineland marina and boat slip. Berths at the marina are south of the boat slip. Depths of 6½ feet are alongside. Gasoline, diesel fuel, and limited marine supplies are available.

(268) A small-craft facility is on the south side of a canal that leads west from the waterway at **Mile 802.8.**

(271) A yacht basin at **Mile 821.8** has Berthage with electricity, gasoline, diesel fuel, water, ice, a launching ramp, and marine supplies. Depths of 5 feet are in the approaches and alongside.

(273) Daytona Beach, **Mile 830.0**, is a large resort city with stores, motels, hotels, and restaurants. The city has excellent yacht facilities, and marine supplies can be obtained.

(275) South of the bridge at **Mile 830.7**, a marked channel leads westward to City Dock on the north side of the Municipal Yacht Basin. The channel had a depth of 5½ feet on the centerline. There are berths on the east and south sides with depths of 6½ feet. Water, ice, and electricity are available; meals and lodging are nearby. At the Halifax River Yacht Club, reciprocal courtesies are extended to members of other yacht clubs. Berths with electricity, water, and ice are available. A depth of 8 feet was alongside.

(276) At **Mile 831.0**, a dredged channel marked by daybeacons leads to a small-craft harbor. The depths were 8 feet in the entrance channel and basin

81) The primary facilities for yachts, other than the Halifax River Yacht Club is 0.3 mile south of Seabreeze Bridge at **Mile 829.4**, and is used for docking, and fueling.

(282) The entrance channel to the other marina leaves the Intracoastal Waterway at Mile 831.2, has a marked channel, which had a depth of 7 feet. There are 350 berths. Depths of 7 feet are alongside, and gasoline, diesel fuel, water, ice, electricity, and marine supplies are available. (283) Port Orange. The boatyard 0.3 mile north of the bridge and the marina adjacent to the bridge have berths with electricity, gasoline, diesel fuel, water, ice and marine supplies. Depths of 8 feet and 3 feet are alongside the boatyard and marina.

(285) **Inlet Harbor**. The depth from the waterway to the harbor was 6 feet; thence 5 feet to **Ponce Inlet**. The channel is along the north shore and is not marked. The wharf at Inlet Harbor has depths of 8 feet. Berthage with electricity, gasoline, diesel fuel, water, ice, marine supplies and wet and dry storage are available.

(286) At **Ponce Inlet** there are small-craft facilities where berthage with electricity, gasoline, diesel fuel, water, ice, launching ramps. (290) At **New Smyrna Beach** are small-craft facilities and the Municipal

(290) At **New Smyrna Beach** are small-craft facilities and the Municipal Yacht Basin.

(296) Regulated speed zones for the protection of manatees are in Haulover Canal and in Bairs Cove on the southeast side of the canal. (299) **Merritt Island National Wildlife Refuge** is on the east side of the northern part of Indian River.

(300) At **Mile 876.6**, a causeway and railroad bridge has a clearance of 7 feet. The span is normally in the open position, but will close on the approach of trains.

NOTE D Due to continuous shoal ing between mile marker 1775 and 780 the IAWW magenta course line is not being charted.

NOTE B

The daybeacons are private and positions are approximate.

NOTE B / The daybeacons are private and positions are approximate.



HEIGHTS

Heights in feet above Mean High Water.

NOTE C

Entrances to inlets

The channels are subject to continual changes. Entrance buoys are not charted because they are frequently shifted in specified.

CAUTION

Temporary changes or defects in aids to navigation are not indicated on this chart. See Local Notice to Mariners.

Improved channels shown by broken lines are subject to shoaling, particularly at the edges

CAUTION

Small craft should stay clear of large com-mercial and government vessels even if small craft have the right-of-way.

SUPPLEMENTAL INFORMATION Consult U.S. Coast Pilot 4 for important supplemental information.

WARNING

The prudent mariner will not rely solely on any single aid to navigation, particularly on floating aids. See U.S. Coast Guard Light List and U.S. Coast Pilot for details.

BASCULE BRIDGE CLEARANCES
For bascule bridges, whose spans do not open to a full upright or vertical position, unlimited vertical clearance is not available for the entire charted horizontal clearance.

Improved channels shown by broken lines are subject to shoaling, particularly at the edges.

WARNING

The prudent mariner will not rely solely on any single aid to navigation, particularly on floating aids. See U.S. Coast Guard Light List and U.S. Coast Pilot for details.

HORIZONTAL DATUM

The horizontal reference datum of this chart The horizontal reference datum of this chart is North American Datum of 1983 (NAD 83), which for charting purposes is considered equivalent to the World Geodetic System 1984 (WGS 84). Geographic positions referred to the North American Datum of 1927 must be corrected an average of 0.995 northward and 0.804" eastward to agree with this chart.

AIDS TO NAVIGATION

Consult U.S. Coast Guard Light List for supplemental information concerning aids to

SECURITY ZONE Regulations are published in Chapter 10, (Cape Canaveral Chart, 11484) U.S. Coast Pilot 4.

BACING BUOYS

Racing buoys within the limits of this chart are not shown hereon. Information may be obtained from the U.S. Coast Guard District Offices as racing and other private buoys are not all listed in the U.S. Coast Guard Light List

NOTE A

Novigation regulations are published in Chapter 2, U.S. Coast Pilot 4. Additions or revisions to Chapter 2 are published in the Notices to Mariners. Information concerning the regulations may be obtained at the Office of the Commander, The coast Guard District in Miami, Fla., or at the Office of the District Engineer, Corps of Engineers in Jacksonville, Fla.

Refer to charted regulation section numbers.

(based on NAD 1927)

The Florida State Grid, east zone, is indicated on this chart at ______ The last three digits are omitted.

RADAR REFLECTORS

Radar reflectors have been placed on many floating aids to navigation. Individual radar reflector identification on these aids has been omitted from this chart

NOTE A

NOTE A
Navigation regulations are published in Chapter 2, U.S. Coast Pilot 4. Additions or revisions to Chapter 2 are published in the Notices to Mariners. Information concerning the regulations way be obtained at the Office of the Commander, 7th Coast Guard District in Marin, Fia., or at the Office of the District Engineer, Corps of Engineers in Jacksonville, Fia.

Refer to charted regulation section ourselves.

Refer to charted regulation section numbers.

AIDS TO NAVIGATION

Consult U.S. Coast Guard Light List for optemental information concerning aids to supplemer navigation

INTRACOASTAL WATERWAY AIDS

The U.S. Aids to Navigation System is designed for use with nautical charts, and the exact meaning of an aid to navigation may not be clear unless the appropriate chart is consulted. Aids to navigation marking the Intracoastal Waterway exhibit unique yellow symbols to distinguish them from aids marking other waterways.

ways.

When following the Intracoastal Waterway southward from Norfolk, VA to Cross Bank in Florida Bay, aids with yellow triangles should be kept on the starboard side of the vessel and aids with yellow squares should be kept on the port side of the vessel.

A horizontal yellow band provides no lateral information, but simply identifies aids to navigation as marking the Intracoastal Waterway.

SUPPLEMENTAL INFORMATION

Consult U.S. Coast Pilot 4 for important supplemental information.

CAUTION

Temporary changes or defects in aids to navigation are not indicated on this chart. See Local Notice to Mariners.

PLANE COORDINATE GRID (based on NAD 1927)

The Florida State Grid, east zone, is in-

dicated on this chart at 10,000 foot intervals thus:

The last three digits are omitted

SUBMARINE PIPELINES AND CABLES Charted submarine pipelines and submarine cables and submarine pipeline and cable areas are shown as:

Additional uncharted submarine pipelines and submarine cables may exist within the area of this chart. Not all submarine pipelines and sub-marine cables are required to be buried, and those that were originally buried may have become exposed. Mariners should use extreme caution when operating vessels in deather of caution when operating vessels in depths of water comparable to their draft in areas where pipelines and cables may exist, and when anchoring, dragging, or trawling.

Covered wells may be marked by lighted or which there is a second to the control of the control

Corrected through NM Aug. 11/07. LNM Aug. 07/07

NOTE S

NOIE S
Regulations for Ocean Dumping Sites are contained in 40 CFR, Parts 220-229. Additional information concerning the regulations and requirements for use of the sites may be obtained from the Environmental Protection Agency (FPA, See U.S. Coast Pilots appendix for addresses of EPA offices. Dumping subsequent to the survey dates may have reduced the depths shown.

HORIZONTAL DATUM

Table of Selected Chart Notes

The horizontal reference datum of this chart is North American Datum of 1983 (NAD 83), which for charting purposes is considered equivalent to the World Geodetic System 1984 (WGS 84). Geographic positions referred to the North American Datum of 1927 must be corrected an average of 0.995" northward and 0.804" eastward to agree with this chart.

CAUTION

WARNINGS CONCERNING LARGE VESSELS

WARNINGS CONCERNING LARGE VESSELS

The 'Rules of the Road' state that recreational boats shall not impede the passage of a vessel that can navigate only within a narrow channel or fairway. Large vessels may appear to move slowly due to their large size but actually transit at speeds in excess of 12 knots, requiring a great transit at speeds in excess of 12 knots, requiring a great distance in which to maneuver or stop. A large vessel's superstructure may block the wind with the result that saliboats and saliboards may unexpectedly find themselves unable to maneuver. Bow and stern waves can be hazardous to small vesselssl. Large vessels may not be able to see small craft close to their bows.

SAFETY HINTS

- Keep your chart up to date by applying all Notices to
- Mariners corrections when you receive them.

 2. Read carefully all notes printed on your chart, each is

- 2. Read carefully all notes printed on your chart, each is vitial to your safety affoat.
 3. Learn the meaning of each symbol and abbreviation on your chart from Chart No. 1.
 4. The compass on your chart shows the variation from true north however, you must also correct your bearing for the deviation of your boat.
 5. Constantly use your chart from the beginning to end each trip. Keep in mind the orientation of your boat with respect to the chart.
 6. Maintain your position on the chart by relating charted.
- Maintain your position on the chart by relating charted features with those you can identify in your surroundings.

INTRACOASTAL WATERWAY AIDS

The U.S. Aids to Navigation System is designed for use with nautical charts and the exact meaning of an aid to navigation may not be clear unless the appropriate chart

is consulted.

Alds to navigation marking the intracoastal Waterway exhibit unique yellow symbols to distinguish them from aids marking other waterways.

When following the Intracoastal Waterway southward from Norfolk, V4 to Cross Bank in Florida Bay, aids with yellow triangles should be kept on the starboard side of the vessel and aids with yellow squares should be kept on the port side of the vessel.

A horizontal yellow band provides no lateral information, but simply identifies aids to navigation as marking the Intracoastal Waterway.

NOTE H

The heavy dashed magenta lines represent launch hazard areas associated with the majority of launches from Cape Canaveral. Launch debris may fall within these areas. See Notice to Mariners or contact the Coast Guard for launch hazard areas specific to each launch and the times they will be in effect.

HURRICANES AND TROPICAL STORMS

HURRICANES AND INCIDENT INTEREST TO THE ALTONOMY AND A CAUSE CONSIDERATION AND A CAUSE CAUSE

Wrecks and submerged obstructions may have been displaced from charted locations. Pipelines may have become uncovered or moved.

Mariners are urged to exercise extreme caution and are requested to report aids to navigation discrepancies and hazards to navigation to the nearest United States Coast Guard unit.

, Aug./07; Corrected through NM Aug 11/07, LNM Aug. 07/07

., Aug./07; Corrected through NM Aug. 11/07, LNM Aug. 07/07


Additional information can be obtained at nauticalcharts noaa gov.

CAUTION

BASCULE BRIDGE CLEARANCES

For bascule bridges, whose spans do not open to a full upright or vertical position, unlimited vertical clearance is not available for the entire charted horizontal clearance.


MERCATOR PROJECTION AT SCALE 1:40,000 SOUNDINGS IN FEET AT MEAN LOWER LOW WATER NORTH AMERICAN DATUM OF 1983 (WORLD GEODETIC SYSTEM 1984)



1000 0

Yards





This BookletChart was reduced to 75% of the original chart scale. The new scale is 1:53333. Barscales have also been reduced and are accurate when used to measure distances in this BookletChart.

HURRICANES AND TROPICAL STORMS

Hurricanes, tropical storms and other major storms may cause considerable damage to marine structures, aids to navigation and moored vessels, resulting in submerged debris in unknown locations.

navigation and moored vessels, resulting in submerged debris in unknown locations.


Charted soundings, channel depths and shoreline may not reflect actual conditions following these storms. Fixed dids navigation may have been damaged or destroyed. Buoys may have been moved from charted positions, damaged, sunk, extinguished or otherwise made inoperative. Mariners should not rely upon the position or operation of an aid to navigation. Wrecks and submerged obstructions may have been displaced from charted locations. Pipelines may have become uncovered or moved.

from of affect locations. In political in or moved.

Mariners are urged to exercise extreme caution and are requested to report aids to navigation discrepancies and hazards to navigation to the nearest United States Coast Guard

NO	SMALL CRAF
3	SEA LOVE N
ЗА	CAMACHEE COVE ,
-6	ST. AUGUSTINE MUI
14	MARINELANE
15	PALM COAST GOLF I
22	ENGLISH JIM':
24	HALIFAX HARBO
25	DAYTONA N
29	ADVENTURE YAC
32	INLET HARBO
42	NORTH CAUSEV
54C	TITUSVILLE MUNIC
54E	KENNEDY POI
57	HARBORTOWN MARI
57C	HARBOR SQUA
65	PINEDA POINT

THE LOCATION THE TABULATED "APPRO THE TABUL





DEPTHS				SERVIC	ES				$\overline{}$	S	UPPLIE	s	\					
ATT FACILITY	AN CHENT PHE STED	No SURIES CORRES	MAGIN KACIDA KACIDA	SE PAIL MOTOR	H AS ACT ALATE POSICE	BOAT ENTAL Canol L.Tons	CHA! CHOWA!	POD I OU ATERITOR	TOILE SAN SESAN	NACONE STA	HATER CHANGE	A CERCIANT	OKS HARDW	OH, SARK	GREO.	THE STATE OF THE S	\	
AFT FACILITY	/		_\	37		\angle		/.	84	_\	$\overline{}$		\angle	\geq	\setminus	\triangle	\setminus	\sim
E MARINA	Α	15	15	ВΕ					М	С	FL	Р		С	WI	GН	ВТ	DG
/E YACHT HARBOR	Α	7	7	ВΕ		HMB	50	50			FL	TSLP	w	С	WI	GH	ВТ	DG
JUNICIPAL MARINA	Α	20	18	ВЕ								TSLP		С	WI	GH		DG
ND MARINA	A	5	5	BME	S	M				8	FLC	TSLP		С	WI			DG
F RESORT MARINA	A	8	10	ВЕ	S				CRM		FL	TSLP		С	WI	н	BT	DG
IM'S MARINA	A	6	6	ΒЕ								TSLP	WD		WI	Н		DG
RBOR MARINA	Α	8	8	ВЕ	S						F	TSLP	₩		WI			DG
IA MARINA	Α	8	8	ВΕ		HMR		55				TSLP	W	С	WI	н		DG
'ACHT HARBOR	Α	6	10	ВΕ							F	TSLP		С	WI	н		DG
BOR MARINA	Α	6	8	ВЕ							F	TSLP	WD	C	WI	G	В⊤	DG
EWAY MARINE	Α	6	8	В		HMR		10	М			T P	₩D	О	WI	GH	В	DG
NICIPAL MARINA	В	8	8	ВЕ	S							TSLP		С	WI	GН	вт	DG
OINT MARINA	В	6	6	ВΕ	s				CRM	s		TSLP	₩		WI	GH		DG
ARINA & BOATYARD	В	8	8	ВΕ		HMR		70			F	TSLP	WD		WI			DG
UARE MARINA	В	14	7	ВΕ		MR				c s		TSLP	WD	С	WI	Н		D
INT MARINA	В	4	4	вм		HMR		12				T P						D

ONS OF THE ABOVE PUBLIC MARINE FACILITIES ARE SHOWN ON THE CHART BY MAGENTA NUMBERS AND LEADERS. "ROACH-FEET (REPORTEDY IS THE OBETH AVAILABLE FROM THE NARREST NATURAL OR DREDGED ANABLE TO THE FACILITY. JULIATED "PUMP-OUT STATION" IS DEFINED AS FACILITIES AVAILABLE FOR PUMPING OUT BOAT HOLDING TANKS.

RULES OF THE ROAD (ABRIDGED)

Motorless craft have the right-of-way in almost all cases.

Sailing vessels and motorboats less than sixtyfive feet in length, shall not hamper, in a nar-row channel, the safe passage of a vessel which can navigate only inside that channel.

A motorboat being overtaken has the right-of-

Motorboats approaching head to head or nearly so should pass port to port.

When motorboats approach each other at right angles or obliquely, the boat on the right has the right-of-way in most cases.

Motorboats must keep to the right in narrow chan-

nels, when safe and practicable.

Mariners are urged to become familiar with the complete rest of the Rules of the Road in U.S. Coast Guard publication "Navigation Rules".

HORIZONTAL DATUM

The horizontal reference datum of this chart is North American Datum of 1983 (NAD 83), which is Norm American Daum of 1982 (NAU 83), which for charting purposes is considered equivalent to the World Goodctic System 1984 (WGS 84) Geographic positions referred to the North American Datum of 1927 must be corrected an average of 0.995° northward and 0.804" eastward to agree with this chart.

CAUTION

BASCULE BRIDGE CLEARANCES

For bascule bridges, whose spans do not open to a full upright or vertical position, unlimited

Joins vertical clearance is not available for the entire charted horizontal clearance. page 88 ∞ ន 27 56 29 23 G LATITUDE Joins page 13

This BookletChart has been updated with: Coast Guard Local Notice To Mariners: 0710 2/16/2010, NGA Weekly Notice to Mariners: 0910 2/27/2010, Canadian Coast Guard Notice to Mariners: n/a.

INTRACOASTAL WATERWAY Project Depths

12 feet Norfolk, Va. to Fort Pierce, Fla. 10 feet Fort Pierce, Fla. to Miami, Fla. 7 feet Miami, Fla. to Cross Bank, Florida Bay, The controlling depths are published periodically in the U.S. Coast Guard Local Notice to Mariners.

Distances

The Waterway is indicated by a magenta line. Mileage distances along the Waterway are in Statute Miles, southward from Norfolk, Virginia, and indicated thus:

Tables for converting Statute Miles to International Nautical Miles are given in U.S. Coast Pilot 4.

INTRACOASTAL WATERWAY AIDS

The U.S. Aids to Navigation System is designed for use with nautical charts, and the exact meaning of an aid to navigation may not be clear unless the appropriate chart is consulted.

Aids to navigation marking the Intracoastal Waterway exhibit unique yellow symbols to distinguish them from aids marking other waterways. ways

When following the Intracoastal Waterway southward from Norfolk, VA to Cross Bank in Florida Bay, aids with yellow triangles should be kept on the starboard side of the vessel and

be kept on the starboard side of the vessel and aids with yellow squares should be kept on the port side of the vessel. A Forizontal yellow band provides no lateral information, but simply identifies aids to navigation as marking the Intracpastal Waterway.

WARNING

The prudent mariner will not rely solely on any single aid to navigation, particularly on floating a ds. See U.S. Coast Guard Light List and U.S. Coast Pilot for details.

CAUTION

Temporary changes or defects in aids to navigation are not indicated on this chart. See Local Notice to Mariners.

Improved channels shown by broken lines are

subject to shoaling, particularly at the edges.

CAUTION

Small craft should stay clear of large commercial and government vessels even if small craft have the right-of-way.

RACING BUOYS

Racing buoys within the limits of this chart are not shown hereon. Information may be obtained from the U.S. Coast Guard District Offices as racing and other private buoys are not all listed in the U.S. Coast Guard Light List.

AIDS TO NAVIGATION

Consult U.S. Coast Guard Light List for supplemental information concerning aids to


PLANE COORDINATE GRID (based on NAD 1927)

10,000 foot intervals thus:

The last three digits are omitted

NOTE H

The heavy dashed magental lines represent launch hazard areas associated with the majority of launches from Cape Canaveral. Launch debris may fall within these areas. See Notice to Mariners or contact the Coast Guard for launch hazard areas specific to each launch and the times they will be in effect.



CALE 1:40,000 Nautical Miles Printed at reduced scale. See Note on page 5. 1/2 Yards 1000 0 1000 2000 3000 4000 5000

MERCATOR PROJECTION AT SCALE 1.40,000 SOUNDINGS IN FEET AT MEAN LOWER LOW WATER NORTH AMERICAN DATUM OF 1983 (WORLD GEODETIC SYSTEM 1984)

Additional information can be obtained at nauticalcharts.noaa.gov.

AUTHORIT ES

Hydrography and topography by the National Ocean Service, Coast Survey, with additional data from the Corps of Engineers, Geological Survey, and U.S. Coast Guard.

SUPPLEMENTAL INFORMATION

Consult U.S. Coast Pilot 4 for important supplemental information.

HEIGHTS

Heights in feet above Mean High Water.

CAUTION

This chart has been corrected from the Notice to Mariners (NM) published weekly by the National Geospatial-Intelligence Agency and the Local Notice to Mariners (LNM) issued periodically by each U.S. Coast Guard district to the dates shown in the lower left hand corner. Chart updates corrected from Notice to Mariners published after the dates shown in the lower left hand corner are available at nauticalcharts nosa gov.

POLLUTION REPORTS

Report all spills of oil and hazardous substances to the National Response Center via 1-800-424-8302 (toll free), or to the nearest U.S. Coast Guard facility if telephone communication is impossible (33 CFR 153).

PRINT-ON-DEMAND CHARTS

NOAA and its partner, OceanGrafix, offer this chart updated weekly by NOAA for Notices to Mariners and critical corrections. Charts are printed when ordered using Print-on-Demand technology. New Editions are available 5-8 weeks before their release as traditional NOAA charts. Ask your chart agent about Print-on-Demand charts or contact NOAA at 1-800-584-4863, http://NauticalCharts.gov, help@NauticalCharts.gov, or OceanGrafix at 1-877-56CHART, http://OceanGrafix.com, or help@OceanGrafix.or

NAUTICAL CHART 11485



INTRACOASTAL WATERWAY

THE NATION'S CHARTMAKER SINCE 1807

TOLOMATO RIVER TO PALM SHORES

FLORIDA


NON 7040044040050


ED. NC. 35


NSN 7642014010252 NGA REFERENCE NO. 11XHA11485

Chart 11485 35th Ed., Aug/07 ■
Corrected through NM Aug. 11/07. LNM Aug. 07/07

Published at Washington, D.C.
U.S. DEPARTMENT OF COMMERCE
NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION
NATIONAL OCEAN SERVICE
COAST SURVEY








11485 35th Ed., Aug./07; Corrected through NM Aug. 11/07, LNM Aug. 07/07


INTRACOASTAL WATERWAY Project Depths


12 feet Norfolk, VA to Fort Pierce FL; 10 feet Fort Pierce, FL to Miami FL; 7 feet Miami, FL to Cross Bank, Florida Bay. The controlling depths are published periodically in the U.S. Coast Guard Local Notice to Mariners.

Joins page 16 Strong tidal currents exist perpendicular to the Bridge Lions opening. Vessels engaged in towing and pushing

MARINE









Printed at reduced scale.

SCALE 1:40,000
Nautical Miles


See Note on page 5.

Yards
1000 0 1000 2000 3000 4000 5000










H1. Drime H1. Drime H1.	
0.4 1 0622 2.4 16 0026 2.5 0.1 1 1016 2.2 -2.6 9.0026 2.5 2.3 1016 2.3 1249 2.0 12.3 12.5 12.5 12.5 12.5 12.5 12.5 12.5 12.5	
2.3 1936 2.3	
2.3 1936 2.3	
0.4 2 0055 0.0 17 018 0.4 2.1 W 0729 2.5 Th 0726 2.1 -0.1 1317 -0.6 1330 0.0 2.5 2012 2.6 2017 2.4	



11485 35th Ed., Aug./07; Corrected through NM Aug. 11/07, LNM Aug. 07/07

INTRACOASTAL WATERWAY

Project Depths

12 feet Norfolk, VA to Fort Pierce FL; 10 feet Fort Pierce, FL to Miami FL; 7 feet Miami, FL to Cross Bank, Florida Bay. The controlling depths are published periodically in the U.S. Coast Guard Looal Notice to Mariners.

The Waterway is indicated by a magenta line. Mileage distances along the waterway are in Statute Miles, southward from Norfolk, Virginia, and

indicated thus:

Tables for converting Statute Miles to International Nautical Miles are given in U.S. Coast Pilot 4.

INTRACOASTAL WATERWAY AIDS

The U.S. Aids to Navigation System is designed for use with nautical charts and the exact meaning of an aid to navigation may not be clear unless the appropriate chart

is consulted.

Aids to navigation marking the Intracoastal Waterway exhibit unique yellow symbols to distinguish them from aids marking other waterways.

When following the Intracoastal Waterway southward from Norfolk, VA to Cross Bank in Florida Bay, aids with yellow triangles should be kept on the starboard side of the vessel and aids with yellow squares should be kept on the port side

A horizontal yellow band provides no lateral information, but simply identifies aids to navigation as marking the Intracoastal Waterway.

WARNING

The prudent mariner will not rely solely on any single aid to navigation, particularly on floating aids. See U.S. Coast Guard Light List and U.S. Coast Pilot for details.

NOTE F

Strong tidal currents exist perpendicular to the Bridge of Lions opening. Vessels engaged in towing and pushing operations are advised to transit the bridge opening during slack tide and, if necessary, breakdown the tow in small units or use adequate tugs.

ABBREVIATIONS (For complete list of Symbols and Abbreviations, see Chart No. 1.) Aids to Navigation (lights are white unless otherwise indicated):

AERO aeronautical	G green	Mo morse code	R TR radio towo
Al alternating	IQ interrupted quick	N nun	Rot rotating
B black	Iso isophase	CBSC obscured	s seconds
Bn beacon	LT HO lighthouse	Co occulting	SEC sector
C can	M nautical mile	Or orange	St M statute mile
DIA diaphone	m minutes	Q quick	VQ very quick
F fxed	MICRO TR microwave tower	P. red	W white
FI flashing	Mkr marker	Fa Ref radar reflector	WHIS whistle
v		Fi Bn radiobeacon	Y yellow
m coaracteristics			

Bottom characteristics:				
Blcs boulders	Co coral	gy gray	Oys oysters	so soft
bk broken	G gravel	h hard	Rk rock	Sh shells
Cy clay	Grs grass	M mud	\$ sand	sy sticky

Miscellaneous: AUTH authorized PD position doubtful Subm submerged Obstruction


ED existence doubtful PA position approximate Rep reported

21. Wrock, rock, obstruction, or shoel sworpt clear to the depth indicated.

(2) Rocks that cover and uncover, with heights in feet above datum of soundings. COLREGS: International Regulations for Preventing Collisions at Sea, 1972. Demarcation lines are shown thus:

FACILITIES

Locations of public marine facilities are shown by large magenta numbers with leaders and refer to the facility tabulation.



CALE 1:40,000 Nautica<u>l Miles</u> Printed at reduced scale. See Note on page 5. Yards 1000 0 1000 2000 3000 4000 5000

MARINE NATION Jackson Melbour Miami, F *Record

WEATH

CITY Mayport, Miami, El

*Local Ti +Proced

NE WEATHER FORECASTS DNAL WEATHER SERVICE sonville, FL ourne, FL i, FL

TELEPHONE NUMBERS 0FFICE HOURS (**904) 741-4311 8:30 AM-5:00PM (Mon-Fri) (**321) 255-0212 8:00 AM-4:00 PM (Mon-Fri) (**305) 229-4522 24 Hours daily

orded (24 Hours daily)

THER INFORMATION BY MARINE RADIOTELEPHONE

STATION FREQUENCY DAILY BROADCAST-EST SPECIAL WARNING

2670 kHz 1:20 a.m. & p.m. 7:15 a.m. & 5:15 p.m. +On Receipt NMA-10 157.1 MHz +On Receipt , Fla NCE 2670 kHz *10:50 a.m. & p.m.

1 Times

eded by Announcement on 2182 kHz/156.8 MHz

CONTINUOUS MARINE BROADCASTS

STATION FREQUENCY BROADCAST TIMES CITY KH3-39 KIH-26 162.55 MHz 162.40 MHz 24 Hours Daily Jacksonville, Fla. Daytona Beach, Fla 24 Hours Daily Melbourne, Fla. WXJ-70 162.55 MHz 24 Hours Daily

WEATHER RULES FOR SAFE BOATING

Before setting out:

Check local weather and sea conditions.

Obtain the latest weather forecast for your area from radio broadcasts.


When warnings are in effect, don't go out unless you are con'ident your boat can be navigated safely under forcast conditions of wind and sea. While afloat:

 Keep a weather eye out for:
 A A sudden vertical cumulus cloud development
 B. A sudden change in wind direction
 C. A sudden noticeable increase in wind velocity
 D. A Drop in temperature
 Be alert to heavy static on your AM radio which may indicate approaching thunderstorms. thunderstorms

3. Check radio weather broadcasts for latest forcasts and warnings

Thunder squalls often occur on warm, moist afternoons and are a great hazard to the mariner. They can have wind gusts up to 80 mph and hit almost without warning. To survive a squall, you must prevent being capsized or blow to leeward into danger.

Joins page 1 bootmen, cond -USPS-Local Squa N.C. 27612, 919-82 USCGAUX - 7th C or USCG Headquart



UJoins page 12

SAFETY HINTS

- Keep your chart up to date by applying all Notices to Mariners corrections when you receive the

- Mariners corrections when you receive them.

 2. Read carefully all notes printed on your chart, each is sital to your safety affoat

 3. Learn the meaning of each symbol and abbreviation on your chart from Chart No. 1.

 4. The compass on your chart shows the variation from true north however, you must also correct your bearing for the deviation of your boat.
- 5. Constantly use your chart from the beginning to end of each trip. Keep in mind the orientation of your boat with respect to the chart.
- Maintain your position on the chart by relating charted features with those you can identify in your surroundings.

ACKNOWLEDGMENT

The National Ocean Service acknowledges the exceptional cooperation received from members of Flotilla 070-04-06 of the United States Coast Guard Auxiliary for continually providing essential information for revising this chart.

PUBLIC BOATING INSTRUCTION PROGRAMS

The United States Power Squadrons and U. S. Coast Guard Auxiliary, national organizations of bootmen, conduct extensive booting instruction programs in communities throughout the United States. For information regarding these educational courses, contact the following sources: LSPS-Local Squadron Commander or USPS Headquarters, Post Office Box 30423, Raleigh, N.C. 27612, 919-821-0281.

USCGAUX - 7th Coast Guard District, 51 Southwest First Ave., Mami, Fla. 33130, 305-350-5697 or USCG Headquarters (G-BAU), Washington, D.C. 20593-0001.

HORIZONTAL DATUM

The horizontal reference datum of this chart is North American Datum of 1983 (NAD 83), which for charting purposes is considered equivalent to the World Geodetic System 1984 (WGS 84). Geographic positions referred to the North American Datum of 1927 must be corrected an average of 0.995" northward and 0.804" eastward to agree with this chart.


CAUTION

BASCULE BRIDGE CLEARANCES


For bascule bridges, whose spans do not open to a full upright or vertical position, unlimited vertical clearance is not available for the entire charted horizontal clearance.

NOTE S

Regulations for Ocean Dumping Sites are contained in 40 CFR, Parts 220-229. Additional information concerning the regulations and requirements for use of the sites may be obtained from the Environmental Protection Agency (EPA). See U.S. Coast Pilots appendix for addresses of EPA offices. Dumping subsequent to the survey dates may have reduced the depths shown.







CAUTION

SUBMARINE PIPELINES AND CABLES

Charted submarine pipelines and submarine cables and submarine pipeline and cable areas are shown as:

~~~~~ Pipeline Area Cable Area

Additional uncharted submarine pipelines and Additional uncharted submarine pipelines and submarine cables may exist within the area of this chart. Not all submarine pipelines and submarine cables are required to be burled, and those that were originally burled may have become exposed. Mariners should use extreme caution when operating vessels in depths of water comparable to their draft in areas where pipelines and sables may exist, and when anchoring, draggling, or trawling.


Covered wells may be marked by lighted or unlighted buoys.


#### RADAR REFLECTORS


Radar reflectors have been placed on many floating aids to navigation. Individual radar reflector identification on these aids has been omitted from this chart.

This nautical chart has been designed to promote safe navigation. The National Ocean Service encourages users to submit corrections, additions, or comments for improving this chart to the Chief, Martine Charl Division (N/CS2), National Ocean Service, NOAA, Silver Spring, Maryland 20910-3282.

| AL                                 | GUST                      | 2007                               |                           | SEF                                | TEME                      | 3ER 2007                            |                           | α                                  | R 2007                   | NOVEMBER 2007                      |                           |                                    |                          |                                     |                           |
|------------------------------------|---------------------------|------------------------------------|---------------------------|------------------------------------|---------------------------|-------------------------------------|---------------------------|------------------------------------|--------------------------|------------------------------------|---------------------------|------------------------------------|--------------------------|-------------------------------------|---------------------------|
| Time                               | Ht.                       | Time<br>Day                        | Ht.                       | Time<br>Day                        | Ht,                       | Time<br>Day                         | Ht,                       | Time<br>Day                        | Нt,                      | T Ime<br>Day                       | Ht.                       | Time                               | H1.                      | Time<br>Day                         | Hŧ.                       |
| h.m.                               | ft.                       | h.m.                               | rt.                       | h.m.                               | ٠t.                       | h.m.                                | ft.                       | h.m.                               | It.                      | h.m.                               | ft.                       | h.m.                               | rt.                      | h.m.                                | ft.                       |
| 1 0328<br>W 1008<br>1547<br>2229   | -0.1<br>2.6<br>0.1<br>2.7 | 16 0408<br>Th 1038<br>1627<br>2251 | 3.2<br>2.5<br>3.3<br>2.5  | 1 0439<br>Se 1127<br>1706<br>2335  | -0.1<br>3.0<br>0.3<br>2.8 | 16 0440<br>Su 1121<br>1703<br>2322  | 0.5<br>2.8<br>0.9<br>2.5  | I 0513<br>N 1294<br>1748           | 0.1<br>3.1<br>0.7        | 16 0441<br>Tu 1136<br>1710<br>2334 | 0.7<br>2.7<br>1.1<br>2.5  | 1 0100<br>Th 9704<br>1347<br>1946  | 2.7<br>0.5<br>2.8<br>0.8 | 16 0005<br>F 0552<br>1250<br>1834   | 2.4<br>0.6<br>2.0<br>0.9  |
| 2 9414<br>Th 1055<br>1636<br>2313  | -0.1<br>2.6<br>0.0<br>2.6 | 17 0447<br>F 1117<br>1706<br>2325  | 2.5<br>2.5<br>2.4         | 2 0533<br>Su 1222<br>1805          | -0.1<br>2.9<br>0.5        | 17 0518<br>M 1204<br>1744           | 0.5<br>2.5<br>1.0         | 2 0013<br>Tu 0815<br>1305<br>1853  | 2.9<br>0.3<br>2.9<br>0.8 | 17 0525<br>W 1224<br>1759          | 0.8<br>2.6<br>1.2         | 2 020B<br>F 0813<br>1449<br>2052   | 2.6<br>0.7<br>2.7<br>0.8 | 17 0104<br>Sa 0853<br>1343<br>1936  | 2.3                       |
| 3 0503<br>F 1146<br>1727<br>2359   | 2.6<br>2.6<br>2.6         | 18 0525<br>Sa 1158<br>1746         | 2.4<br>3.6                | 3 0029<br>M 0632<br>1323<br>1908   | 2.7<br>0.1<br>2.7<br>0.7  | 18 0003<br>Tu 0603<br>1253<br>1833  | 2.4<br>0.7<br>2.4<br>1.1  | 3 0116<br>W 0723<br>1412<br>2004   | 2.7<br>0.5<br>2.8<br>0.9 | 18 0324<br>Th 0320<br>1319<br>1301 | 2.4<br>0.8<br>2.5<br>1.2  | 3 0316<br>Se 0918<br>1549<br>2150  | 2.6<br>0.7<br>2.7<br>0.7 | 18 0208<br>Su 0800<br>1439<br>2039  | 2.4                       |
| 4 0555<br>Se 1241<br>1823          | -0.2<br>2.6<br>0.2        | 19 0002<br>Su 0607<br>1242<br>1830 | 2.3<br>5.4<br>2.3<br>3.8  | 4 0129<br>Tu 0736<br>1429<br>2017  | 2.6<br>2.8<br>0.8         | 19 0051<br>W 0656<br>1351<br>1935   | 2.3<br>0.8<br>2.4<br>1.2  | 4 0228<br>Th 0835<br>1520<br>2114  | 2.7<br>0.8<br>2.7<br>0.9 | 19 0124<br>F 0725<br>1419<br>2309  | 2.4<br>0.9<br>2.5<br>1.1  | 4 0420<br>Su 1015<br>1842<br>2241  | 2.6<br>0.7<br>2.7<br>0.6 | 19 0314<br>M 0905<br>1535<br>2136   | 2.5<br>0.6<br>2.6<br>0.4  |
| 5 9049<br>50 0652<br>1340<br>1924  | 2.5<br>2.5<br>0.4         | 20 0043<br>M 0653<br>1331<br>1921  | 2.2<br>2.5<br>2.2<br>3.9  | 5 0237<br>W 0848<br>1539<br>2126   | 2.5<br>0.3<br>2.6<br>0.8  | 20 0150<br>Th 0803<br>1455<br>2044  | 2.3<br>0.6<br>2.4<br>1.2  | 5 0338<br>F 0942<br>1623<br>2216   | 2.7<br>0.6<br>2.8<br>0.0 | 20 0232<br>58 0534<br>1319<br>2113 | 2.4<br>0.8<br>2.6<br>1.0  | 5 9514<br>M 1105<br>1728<br>2325   | 2.7<br>0.7<br>2.7<br>0.5 | 20 0417<br>Tu 1005<br>1630<br>2231  | 2.7                       |
| 6 0145<br>M 0754<br>1444<br>2030   | 2.4<br>-0.1<br>2.4<br>0.5 | 21 0190<br>Tu 0747<br>1428<br>2020 | 2.1<br>5.5<br>2.1<br>3.9  | 6 0349<br>Th 0955<br>1646<br>2231  | 2.5<br>0.3<br>2.8<br>0.7  | 21 0256<br>F 0910<br>1558<br>2148   | 2.3<br>0.8<br>2.5<br>1.0  | 6 0444<br>Sa 1041<br>1719<br>2309  | 2.7<br>0.6<br>2.8<br>0.7 | 21 0341<br>Su 0338<br>1918<br>2210 | 2.6<br>0.8<br>2.7<br>0.7  | 6 0801<br>Tu 1150<br>1809          | 2.8<br>0.7<br>2.7        | 21 0517<br>W 1103<br>1725<br>2323   | 2.9<br>0.4<br>2.6<br>-0.1 |
| 7 0248<br>Tu 0859<br>1552<br>2138  | 2.3<br>2.4<br>0.5         | 22 0225<br>W 0647<br>1531<br>2123  | 2.1<br>3.5<br>2.2<br>3.9  | 7 0457<br>F 1056<br>1744<br>2328   | 2.6<br>0.3<br>2.7<br>0.6  | 22 0407<br>\$6 1011<br>1656<br>2243 | 2.4<br>0.6<br>2.6<br>0.8  | 7 0540<br>Su 1132<br>1806<br>2355  | 2.8<br>0.6<br>2.8<br>0.6 | 22 0444<br>M 1038<br>1708<br>2301  | 2.6<br>0.6<br>2.5         | 7 0004<br>W 0649<br>1230<br>1847   | 0.4<br>2.8<br>0.7<br>2.7 | 22 0613<br>Th 1156<br>1818          | 3.1<br>0.1<br>2.9         |
| 8 0356<br>W 1004<br>1659<br>2240   | 2.3<br>-0.1<br>2.5<br>0.5 | 23 0329<br>Th U947<br>1635<br>2222 | 2.1<br>2.5<br>2.2<br>3.9  | 8 0357<br>Sa 1150<br>1834          | 2.7<br>0.3<br>2.8         | 23 0509<br>Su 1105<br>1747<br>2333  | 2.8<br>0.5<br>2.8<br>0.8  | 6 G628<br>N 1217<br>1846           | 2.9<br>0.6<br>2.9        | 23 0541<br>Tu 1129<br>1758<br>2350 | 3.0<br>0.5<br>3.0<br>0.2  | 8 0642<br>Th 0721<br>1307<br>1923  | 0.4<br>2.9<br>0.7<br>2.7 | 23 0015<br>F 0707<br>1248<br>1911   | 0.3                       |
| 9 0504<br>Th 1105<br>1800<br>2339  | 2.4<br>-0.1<br>2.5<br>0.4 | 24 0435<br>F 1043<br>1732<br>2315  | 2.2<br>3.4<br>2.4<br>3.7  | 9 0017<br>Su 0646<br>1236<br>1918  | 0.5<br>2.8<br>0.3<br>2.8  | 24 0606<br>M 1156<br>1834           | 2.9<br>0.4<br>3.0         | 9 0005<br>Tu 0710<br>1258<br>1923  | 0.5<br>3.0<br>0.6<br>2.9 | 24 0334<br>W 1219<br>1347          | 5,2<br>0.4<br>3.1         | 9 0117<br>F 0758<br>1344<br>1959   | 0.0<br>2.9<br>0.7<br>2.7 | 24 0105<br>\$8 0759<br>1339<br>2003 | 3.2                       |
| ID 0806<br>F 1202<br>1854          | 2.4                       | 25 0535<br>Se 1134<br>1823         | 2.3<br>3.3<br>2.5         | 10 0102<br>M 0733<br>1322<br>1956  | 0.4<br>2.8<br>0.3<br>2.9  | 25 0020<br>Tij 0657<br>1244<br>1919 | 0.3<br>3.1<br>0.3<br>3.1  | 10 0113<br>W 0749<br>1335<br>1957  | 0.4<br>3.0<br>0.6<br>2.9 | 25 0338<br>Th 0725<br>1308<br>1935 | 0.0<br>3.4<br>0.3<br>3.2  | 10 0152<br>Sa 0635<br>1419<br>2036 | 0.3<br>2.9<br>0.7<br>2.7 | 25 0158<br>Su 0851<br>1430<br>2066  | 3.0                       |
| 11 0033<br>Se 0701<br>1254<br>1942 | 0.3<br>2.5<br>0.1<br>2.7  | 26 0004<br>Su 0630<br>1222<br>1909 | 3.6<br>2.5<br>3.1<br>2.7  | II 0142<br>Tu 6614<br>1402<br>2032 | 0.3<br>2.9<br>0.3<br>2.9  | 26 0105<br>W 0747<br>1331<br>2004   | 0.1<br>3.3<br>0.2<br>3.2  | 11 0148<br>Th 0825<br>1411<br>2031 | 0.4<br>3.0<br>0.7<br>2.9 | 26 0126<br>F 0816<br>1357<br>2323  | -0.2<br>5.5<br>0.3<br>3.2 | 11 0227<br>Su 0912<br>1453<br>2112 | 0.3<br>2.9<br>0.8<br>2.6 | 26 0250<br>M 0942<br>1522<br>2149   | 0.200                     |
| 12 0122<br>Su 0751<br>1341<br>2025 | 0.2<br>2.6<br>-0.1<br>2.7 | 27 0049<br>M 0721<br>1309<br>1953  | 3.4<br>2.7<br>3.0<br>2.9  | 12 0219<br>W 0853<br>1440<br>2105  | 0.3<br>2.9<br>0.4<br>2.8  | 27 0151<br>Th 0936<br>1418<br>2049  | -0.1<br>3.4<br>0.2<br>3.2 | 12 0222<br>F 0900<br>1446<br>2104  | 0.4<br>3.0<br>0.7<br>2.8 | 27 0215<br>Sa 0906<br>1447<br>2113 | 0.2<br>5.5<br>0.3<br>3.2  | 12 0301<br>M 0951<br>1529<br>2150  | 0.4<br>2.8<br>0.8<br>2.5 | 27 0343<br>Tu 1084<br>1617<br>2243  | 3.0<br>0.3<br>2.6         |
| 13 0207<br>M 0837<br>1425<br>2104  | 0.2<br>2.6<br>0.0<br>2.7  | 28 0134<br>Tu 0810<br>1354<br>2035 | 3.2<br>2.9<br>3.0<br>2.9  | 13 0255<br>Th 0929<br>1516<br>2139 | 0.3<br>2.9<br>0.5<br>2.8  | 28 0237<br>F 0925<br>1506<br>2135   | 0.1<br>3.4<br>0.3<br>3.2  | 13 0255<br>Se 0936<br>1519<br>2138 | 0.4<br>3.0<br>0.8<br>2.7 | 28 0306<br>Su 0958<br>1538<br>2204 | -0.2<br>3.4<br>0.4<br>3.1 | 13 0337<br>Tu 1032<br>1605<br>2230 | 0.4<br>2.7<br>0.9<br>2.5 | 28 0438<br>W 1126<br>1714<br>2345   | 0.0<br>2.9<br>0.4<br>2.6  |
| 14 0249<br>Tu 0919<br>1507<br>2141 | 0.1<br>2.6<br>0.1<br>2.7  | 29 0215<br>W 0658<br>1440<br>2118  | 3.0<br>3.0<br>3.0<br>3.0  | 14 0330<br>F 1005<br>1351<br>2212  | 0.3<br>2.8<br>0.6<br>2.7  | 29 0326<br>Sa 1015<br>1556<br>2223  | -0.1<br>3.4<br>0.4<br>3.1 | 14 0329<br>Su 1013<br>1554<br>2214 | 0.5<br>2.9<br>0.9<br>2.7 | 29 0359<br>M 1351<br>1832<br>2259  | 0.0<br>5.3<br>0.8<br>3.0  | 14 G415<br>W 1115<br>1648<br>2315  | 0.5<br>2.6<br>0.9<br>2.4 | 29 0585<br>Th 1219<br>1814          | 0.2<br>2.7<br>0.6         |
| 15 0330<br>W 0959<br>1548<br>2215  | 0.1<br>2.6<br>0.2<br>2.6  | 30 0303<br>Th 0946<br>1527<br>2201 | 3.1<br>3.0<br>3.0         | 15 0405<br>Se 1042<br>1627<br>2246 | 0.4<br>2.7<br>0.7<br>2.6  | 30 0417<br>Su 1108<br>1649<br>2315  | 0.0<br>3.3<br>0.5<br>3.0  | 15 0403<br>N 1053<br>1629<br>2251  | 0.6<br>2.8<br>1.0<br>2.5 | 30 0455<br>Tu 1146<br>1732<br>2357 | 0.1<br>3.1<br>0.7<br>2.8  | 15 0500<br>Th 1200<br>1737         | 0.6<br>2.6<br>0.9        | 30 0038<br>F 0637<br>1313<br>1915   | 2.6                       |
|                                    |                           | 31 0349<br>F 1035<br>1616<br>2247  | -3.2<br>3.1<br>5.2<br>2.9 |                                    |                           |                                     |                           |                                    |                          | 21 0557<br>W 1245<br>1937          | 0.4<br>2.9<br>0.8         |                                    |                          |                                     |                           |








|                           |                                    | JULY                       | 2008                               |                           |
|---------------------------|------------------------------------|----------------------------|------------------------------------|---------------------------|
| н.                        | Time<br>Day                        | Ht.                        | Time<br>Day                        | Ht,                       |
| f1.                       | h.m.                               | n.                         | h.m.                               | rt.                       |
| 0.4<br>2.9<br>0.1<br>2.3  | 1 0623<br>Tu 1222<br>1918          | 2.4<br>-0.6<br>2.7         | 16 0036<br>W 0651<br>1249<br>1936  | 0.5<br>2.1<br>0.0<br>2.3  |
| 0.4<br>2.1<br>-0.1<br>2.5 | 2 0055<br>W 0723<br>1317<br>2012   | 0.0<br>2.5<br>-0.8<br>2.8  | 17 0118<br>Th 0796<br>1390<br>2017 | 0.4<br>2.1<br>0.0<br>2.4  |
| 0.5<br>2.1<br>0.1<br>2.5  | 3 0180<br>Th 0820<br>1412<br>2103  | -0.1<br>2.6<br>-0.6<br>2.8 | 18 0158<br>F 0820<br>1408<br>2056  | 0.3<br>2.2<br>-0.1<br>2.4 |
| 0.3<br>2.1<br>-0.1<br>2.3 | 4 0244<br>F 0914<br>1505<br>2152   | -0.1<br>2.6<br>-0.5<br>2.8 | 19 0236<br>Se 0902<br>1445<br>2134 | 0.3<br>2.3<br>-0.1<br>2.4 |
| 0.3<br>2.1<br>-0.1<br>2.3 | 5 0337<br>58 1007<br>1558<br>2240  | -0.2<br>2.6<br>-0.4<br>2.7 | 20 0314<br>5u 0944<br>1325<br>2211 | 0.2<br>2.5<br>0.0<br>2.4  |
| 0.3<br>2.1<br>0.0<br>2.3  | 6 0429<br>Su 1059<br>1850<br>2326  | -0.2<br>2.5<br>-0.3<br>2.6 | 21 0351<br>M 1027<br>1605<br>2249  | 0.1<br>2.3<br>0.0<br>2.4  |
| 0.3<br>2.1<br>0.0<br>2.3  | 7 0521<br>M 1151<br>1743           | -0.1<br>2.4<br>-0.1        | 22 0431<br>Tu 1111<br>1648<br>2527 | 0.0<br>2.3<br>0.1<br>2.4  |
| 0.2<br>2.1<br>0.1<br>2.2  | 8 0012<br>Tu 0613<br>1242<br>1836  | 2.4<br>-0.1<br>2.3<br>0.1  | 23 0515<br>W 1158<br>1735          | 0.0<br>2.3<br>0.2         |
| 0.2<br>2.1<br>0.2         | 9 0057<br>W 0706<br>1335<br>1930   | 2.0<br>0.0<br>2.2<br>0.3   | 24 0008<br>Th 0603<br>1249<br>1628 | 2.3<br>0.0<br>2.3<br>0.3  |
| 2.2<br>0.1<br>2.1<br>0.2  | 10 0144<br>Th 0756<br>1429<br>2025 | 2.1<br>0.0<br>2.1<br>0.4   | 25 0054<br>F 0658<br>1547<br>1928  | 2.3<br>-0.1<br>2.3<br>0.4 |
| 2.2<br>0.0<br>2.2<br>0.3  | 11 0232<br>F 0851<br>1525<br>2120  | 2.0<br>2.0<br>0.5          | 26 0148<br>Se 0759<br>1451<br>2034 | 2.2<br>-0.1<br>2.3<br>0.4 |
| 2.1<br>-0.1<br>2.2<br>0.3 | 12 0324<br>Se 0943<br>1622<br>2213 | 2.0<br>0.1<br>2.0<br>0.5   | 27 0250<br>Su 0904<br>1559<br>2140 | 2.2<br>-0.1<br>2.4<br>0.4 |
| 2.2<br>-0.2<br>2.3<br>0.3 | 13 0418<br>Su 1093<br>1716<br>2304 | 0.1<br>2.1<br>0.6          | 28 0359<br>M 1009<br>1708<br>2245  | 2.3<br>-0.2<br>2.4<br>0.4 |
| 2.2<br>-0.4<br>2.4<br>0.2 | 14 0511<br>M 1121<br>1906<br>2351  | 0.1<br>2.1<br>0.5          | 29 0509<br>Tu 1111<br>1908<br>2346 | 2.3<br>-0.3<br>2.6<br>0.2 |
| 2.5<br>2.6<br>2.6         | 15 0603<br>Tu 1207<br>1952         | 2.0<br>0.1<br>2.2          | 30 0614<br>W 1210<br>1904          | 2.5<br>-0.4<br>2.7        |
|                           |                                    |                            | 31 0042<br>Th 0713<br>1305<br>1955 | 0.1<br>2.6<br>-0.4<br>2.8 |


#### CAUTION

#### WARNINGS CONCERNING LARGE VESSELS


WARNINGS CONCERNING LARGE VESSELS


The 'Rules of the Road' state that recreational boats shall not impede the passage of a vessel that can navigate only within a narrow channel or fairway. Large vessels may appear to move slowly due to their large size but actually transit at speeds in excess of 12 knots, requiring a great distance in which to maneuver or stop. A large vessel's superstructure may block the wird with the result that sailboats and sallboards may unexpectedly find themselves unable to maneuver. Bow and stem waves can be hazardous to small vessels. Large vessels may not be able to see small craft close to their bows.
























# **EMERGENCY INFORMATION**

#### VHF Marine Radio channels for use on the waterways:

Channel 6 – Inter-ship safety communications.

**Channel 9** – Communications between boats and ship-to-coast.

**Channel 13** – Navigation purposes at bridges, locks, and harbors.

### Channel 16 – Emergency, distress and safety calls

to Coast Guard and others, and to initiate calls to other vessels. Contact the other vessel, agree to another channel, and then switch.

**Channel 22A** – Calls between the Coast Guard and the public. Severe weather warnings, hazards to navigation and safety warnings are broadcast here.

Channels 68, 69, 71, 72 & 78A – Recreational boat channels.

#### **Distress Call Procedures**

- 1. Make sure radio is on.
- 2. Select Channel 16.
- 3. Press/Hold the transmit button.
- 4. Clearly say: "MAYDAY, MAYDAY, MAYDAY."
- Also give: Vessel Name and/or Description; Position and/or Location; Nature of Emergency; Number of People on Board.
- 6. Release transmit button.
- Wait for 10 seconds If no response Repeat MAYDAY Call.

#### HAVE ALL PERSONS PUT ON LIFE JACKETS!!

#### **Mobile Phones** – Call 911 for water rescue.

Coast Guard Mayport SAR – 904-247-7312 Coast Guard Ponce De Leon Inlet – 386-428-9085 Coast Guard Canaveral – 321-868-4200 Coast Guard Atlantic Area Cmd – 757-398-6390 Indiatlantic Fire & Rescue – 321-723-0366 Florida Fish & Wildlife Conservation Comm – 888-404-3922

<u>NOAA Weather Radio</u> – 162.400 MHz, 162.425 MHz, 162.450 MHz, 162.475 MHz, 162.500 MHz, 162.525 MHz, 162.550 MHz.

Getting and Giving Help – Signal other boaters using visual distress signals (flares, orange flag, lights, arm signals); whistles; horns; and on your VHF radio. You are required by law to help boaters in trouble. Respond to distress signals, but do not endanger yourself.



# NOAA CHARTING PUBLICATIONS

Official NOAA Nautical Charts – NOAA surveys and charts the national and territorial waters of the U.S, including the Great Lakes. We produce over 1,000 traditional nautical charts covering 3.4 million square nautical miles. Carriage of official NOAA charts is mandatory on the commercial ships that carry our commerce. They are used on every Navy and Coast Guard ship, fishing and passenger vessels, and are widely carried by recreational boaters. NOAA charts are available from official chart agents listed at: <a href="https://www.NauticalCharts.NOAA.gov">www.NauticalCharts.NOAA.gov</a>.

Official Print-on-Demand Nautical Charts – These full-scale NOAA charts are updated weekly by NOAA for all Notice to Mariner corrections. They have additional information added in the margin to supplement the chart. Print-on-Demand charts meet all federal chart carriage regulations for charts and updating. Produced under a public/private partnership between NOAA and OceanGrafix, LLC, suppliers of these premium charts are listed at <a href="https://www.oceanGrafix.com">www.oceanGrafix.com</a>.

# Official Electronic Navigational Charts (NOAA ENCs®) –

ENCs are digital files of each chart's features and their attributes for use in computer-based navigation systems. ENCs comply with standards of the International Hydrographic Organization. ENCs and their updates are available for free from NOAA at www.NauticalCharts.NOAA.gov.

# Official Raster Navigational Charts (NOAA RNCs<sup>™</sup>) –

RNCs are geo-referenced digital pictures of NOAA's charts that are suitable for use in computer-based navigation systems. RNCs comply with standards of the International Hydrographic Organization. RNCs and their updates are available for free from NOAA at <a href="https://www.NauticalCharts.NOAA.gov">www.NauticalCharts.NOAA.gov</a>.

Official BookletCharts<sup>™</sup> – BookletCharts<sup>™</sup> are reduced scale NOAA charts organized in page-sized pieces. The "Home Edition" can be downloaded from NOAA for free and printed. The Internet address is www.NauticalCharts.gov/bookletcharts.

Official PocketCharts<sup>TM</sup> – PocketCharts<sup>TM</sup> are for beginning recreational boaters to use for planning and locating, but not for real navigation. Measuring a convenient 13" by 19", they have a 1/3 scale chart on one side, and safety, boating, and educational information on the reverse. They can be purchased at retail outlets and on the Internet.

Official U.S. Coast Pilot® – The Coast Pilots are 9 text volumes containing information important to navigators such as channel descriptions, port facilities, anchorages, bridge and cable clearances, currents, prominent features, weather, dangers, and Federal Regulations. They supplement the charts and are available from NOAA chart agents or may be downloaded for free at <a href="https://www.NauticalCharts.NOAA.gov">www.NauticalCharts.NOAA.gov</a>.

Official On-Line Chart Viewer – All NOAA nautical charts are viewable here on-line using any Internet browser. Each chart is up-to-date with the most recent Notices to Mariners. Use these on-line charts as a ready reference or planning tool. The Internet address is www.NauticalCharts.gov/viewer.

Official Nautical Chart Catalogs – Large format, regional catalogs are available for free from official chart agents. Page size, state catalogs are posted on the Internet and can be printed at home for free. Go to <a href="http://NauticalCharts.NOAA.gov/mcd/ccatalogs.htm">http://NauticalCharts.NOAA.gov/mcd/ccatalogs.htm</a>.

Internet Sites: <a href="https://www.Noa.gov">www.Noa.gov</a>, <a href="